

NICKEL ANTI-SEIZE COMPOUND

Page: 1

Compilation date: 09/05/2017

Revision No: 3

## Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: NICKEL ANTI-SEIZE COMPOUND

Product code: 301688

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Thread lubricant and protector.

## 1.3. Details of the supplier of the safety data sheet

Company name: Cedesa Ltd

Chater Lea Buildings

Icknield Way Letchworth Hertfordshire SG6 1WT

UK

Tel: +44 (0) 1462 480764

Fax: +44 (0) 1462 679324

Email: mike.joyce@cedesa.co.uk

## 1.4. Emergency telephone number

Emergency tel: +44 (0) 1462 480764

(office hours only)

# Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 3: H412

Most important adverse effects: Harmful to aquatic life with long lasting effects.

## 2.2. Label elements

Label elements:

Hazard statements: H412: Harmful to aquatic life with long lasting effects.

Precautionary statements: P273: Avoid release to the environment.

P501: Dispose of contents/container to comply with Local, National and International

regulation.

## 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

NICKEL ANTI-SEIZE COMPOUND

Page: 2

## Section 3: Composition/information on ingredients

#### 3.2. Mixtures

## **Hazardous ingredients:**

#### **COPPER PASTE**

EINECS	CAS	PBT / WEL	CLP Classification	Percent
231-159-6	7440-50-8	-	Acute Tox. 4: H302; Aquatic Acute 1:	1-10%
		H400; Aquatic Chronic 2: H411		

#### **GELLING AGENT**

273-219-4	68953-58-2	Substance with a Community	-	1-10%
		workplace exposure limit.		

### Section 4: First aid measures

## 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water. **Eye contact:** Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

# 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

### Section 5: Fire-fighting measures

### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

## 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

### Section 6: Accidental release measures

NICKEL ANTI-SEIZE COMPOUND

Page: 3

## 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details.

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

## 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Wash the spillage site with large amounts of water.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

#### Section 7: Handling and storage

### 7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of dust in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area.Suitable packaging: Must only be kept in original packaging.

## 7.3. Specific end use(s)

Specific end use(s): No data available.

## Section 8: Exposure controls/personal protection

## 8.1. Control parameters

### Hazardous ingredients:

# **COPPER PASTE**

### Workplace exposure limits:

izespilable dust	Res	pirable	dust
------------------	-----	---------	------

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	-	4 mg/m3	-

### **GELLING AGENT**

UK	$0.1 \text{ ma/m}^2$			
UN	0.1 ma/m3	-	-	
	- · · · · · · · · · · · · · · · · · · ·			I .

# **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

## 8.2. Exposure controls

Respiratory protection: Respiratory protective device with particle filter.

Hand protection: Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

NICKEL ANTI-SEIZE COMPOUND

Page: 4

### Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State: Paste
Colour: Black

Odour: Perceptible odour

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Insoluble

Viscosity: No data available.

**Boiling point/range°C:** 400 **Melting point/range°C:** No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: 200 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: No data available.

Relative density: No data available. pH: 7.0

VOC g/l: No data available.

#### 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

## 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

# 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

# **Section 11: Toxicological information**

## 11.1. Information on toxicological effects

Toxicity values: No data available.

NICKEL ANTI-SEIZE COMPOUND

Page: 5

# Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

### **Section 12: Ecological information**

## 12.1. Toxicity

Ecotoxicity values: No data available.

## 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

### 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

# 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

### **Section 14: Transport information**

**Transport class:** This product does not require a classification for transport.

## **Section 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

### Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

NICKEL ANTI-SEIZE COMPOUND

Page: 6

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.
H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.