

SAFETY DATA SHEET
FAST SET STEEL EPOXY RESIN (326)

Page: 1
Compilation date: 10/05/2017
Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: FAST SET STEEL EPOXY RESIN (326)
Product code: 301978

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Part A (resin) of a two pack, epoxy repair paste; to be used only with the corresponding Part B (catalyst) component.

1.3. Details of the supplier of the safety data sheet

Company name: Cedesa Ltd
Chater Lea Buildings
Icknield Way
Letchworth
Hertfordshire
SG6 1WT
UK
Tel: +44 (0) 1462 480764
Fax: +44 (0) 1462 679324
Email: mike.joyce@cedesa.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0) 1462 480764
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; -: EUH205

Most important adverse effects: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects. Contains epoxy constituents. May produce an allergic reaction.

2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H411: Toxic to aquatic life with long lasting effects.
EUH205: Contains epoxy constituents. May produce an allergic reaction.

[cont...]

SAFETY DATA SHEET

FAST SET STEEL EPOXY RESIN (326)

Page: 2

Hazard pictograms: GHS07: Exclamation mark

GHS09: Environmental



Signal words: Warning

Precautionary statements: P264: Wash skin thoroughly after handling.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321: Specific treatment (see information on this label).

P332+313: If skin irritation occurs: Get medical advice/attention.

P337+313: If eye irritation persists: Get medical advice/attention.

P391: Collect spillage.

P501: Dispose of contents/container to comply with local, regional and national regulations.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

EINECS	CAS	PBT / WEL	CLP Classification	Percent
500-033-5	25068-38-6	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	70-90%

ALUMINIUM POWDER (PYROPHORIC)

231-072-3	7429-90-5	Substance with a Community workplace exposure limit.	Water-react. 2: H261; Pyr. Sol. 1: H250	1-10%
-----------	-----------	--	---	-------

3-GLYCIDYLOXYPRPYL TRIMETHOXYSILANE

219-784-2	2530-83-8	-	Eye Irrit. 2: H319	1-10%
-----------	-----------	---	--------------------	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

[cont...]

SAFETY DATA SHEET

FAST SET STEEL EPOXY RESIN (326)

Page: 3

Eye contact: Bathe the eye with running water for 15 minutes. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water whilst lifting the eye lids. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. If unconscious and breathing is OK, place in the recovery position. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and pain. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: No data available.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Ensure adequate ventilation Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Avoid skin and eye contact.

6.2. Environmental precautions

Environmental precautions: Contain the spillage using bunding. Do not discharge into drains or rivers. Immediately inform appropriate authorities.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

[cont...]

SAFETY DATA SHEET
FAST SET STEEL EPOXY RESIN (326)

Page: 4

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Smoking, eating, drinking and the preparation of foodstuffs prohibited where materials are stored or handled.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. For safe storage, store between 5-30 degC. Keep away from direct sunlight. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

ALUMINIUM POWDER (PYROPHORIC)

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	10 mg/m3	30 mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. If necessary, install additional ventilation or exhaust systems in the work areas to maintain dust levels below the recommended occupational limits.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Ensure emissions from ventilation or equipment comply with environmental protection legislation.

[cont...]

SAFETY DATA SHEET
FAST SET STEEL EPOXY RESIN (326)

Page: 5

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste
Colour: Grey
Odour: Ethereal.
Solubility in water: Insoluble
Relative density: 1.2

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: None established.

10.5. Incompatible materials

Materials to avoid: No data available.

10.6. Hazardous decomposition products

Haz. decomp. products: There are no hazardous decomposition products if stored and used according to specifications.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

[cont...]

SAFETY DATA SHEET
FAST SET STEEL EPOXY RESIN (326)

Page: 6

3-GLYCIDYLOXYPRPYL TRIMETHOXY SILANE

ORAL	RAT	LD50	7.01	g/kg
------	-----	------	------	------

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and pain. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: No data available.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 08 04 09

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

[cont...]

SAFETY DATA SHEET
FAST SET STEEL EPOXY RESIN (326)

Page: 7

Section 14: Transport information

14.1. UN number

UN number: UN3077

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT})

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH205: Contains epoxy constituents. May produce an allergic reaction.

H250: Catches fire spontaneously if exposed to air.

H261: In contact with water releases flammable gases.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

[cont...]

SAFETY DATA SHEET

FAST SET STEEL EPOXY RESIN (326)

Page: 8

and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.