

### Product Description

Aqua Stick is a hand-mixable, specialty epoxy putty for repairs to damp, wet areas and underwater surfaces. After mixing, it forms a polymer compound that may be applied underwater (either fresh or salt water) and will bond tenaciously to substrates such as fiberglass, concrete, glass, ceramic, metal, wood, and many plastics.

Each stick contains pre-measured portions of activator and base throughout — no measuring or mixing tools are necessary. The consistency (like modelling clay) eliminates drips and runs, facilitates adhesion to the substrate, and allows the material to be shaped and formed as needed before curing begins. After 60 minutes the application can be drilled, sawed, sanded, carved, and painted.

Aqua Stick cures to an off-white colour. Suitable for interior or exterior use, it is resistant to chemicals, water, and temperature extremes. Aqua Stick contains no solvents or VOCs. It is non-flammable and releases no noxious fumes. It won't shrink or pull away. The unused portion stays fresh for future use when saved in its original package.

#### Repair...

- Decks and hulls
- Pools, hot tubs and spas
- Gouges
- Marine recreational equipment
- Leaking gaskets
- Gutters and tanks

#### Patches...

- Dents / Gouges
- Holes
- The ultimate solution for small or emergency repairs
- Bonds instantly with superior strength
- Saves cost of expensive repairs

### Performance Data\*

SHELF STABILITY AT 24°C, minimum	24 months
SHORE D HARDNESS AT FULL CURE (24 hrs)	70
LAP SHEAR TENSILE STRENGTH	
On steel (1" x 1" x 1/16")	6.2 MPa
On fiberglass (1" x 1" x 1/16")	3.5 MPa
COMPRESSIVE STRENGTH	55 MPa
DENSITY	1.9 gm/cm <sup>3</sup>
SHRINKAGE	<1%
NON-VOLATILE CONTENT	100%
ELECTRICAL RESISTANCE	30,000 megohms
DIELECTRIC STRENGTH	300 volts/mil
UPPER TEMPERATURE LIMITS	
Continuous	121°C
Intermittent	149°C
CHEMICAL RESISTANCE	
Resistant to hydrocarbons, ketones, alcohols, esters, halocarbons, aqueous salt solutions and dilute acids and bases.	

**NOT INTENDED FOR STRUCTURAL APPLICATIONS**

*\* Not to be used for specification purposes.*

### How To Use

Before applying, roughen and clean the area to be repaired and then follow these easy steps.

1. **Cut** or twist off required amount.
2. **Mix** by kneading with fingers to a uniform colour. If mixing is difficult, warm Aqua Stick to room temperature or slightly above.
3. **Apply** to surface to be repaired within 10 minutes of mixing. Force into any cracks or holes and strike off excess material, preferably with a tool moistened with clean water.  
*When applying to a damp, wet or slowly leaking area, work the mixed material forcefully into the surface and apply pressure until adhesion begins to take effect.*

**For best results:** Use damp fingers for easier mixing, application, and a smooth appearance of the cured compound. Remove excess material before hardening begins.

**Curing:** Aqua Stick has a work life of approximately 25 minutes. Functional cure occurs in 60 minutes.

### Health & Safety

Contains Epoxy Resin and Triethylenetetramine.

Exposure may cause allergic reactions. May be harmful if swallowed. Get prompt medical attention if ingested. Eye irritant. If eye contact occurs, rinse with tap water for 5 to 10 minutes. If irritation persists, seek medical care. Skin irritant. Wash hands thoroughly with soap and water after use. If skin irritation occurs, seek medical attention.

**KEEP OUT OF REACH OF CHILDREN.**

**ISSUE No:** 3

**ISSUE DATE:** MARCH 2017

**ISSUED BY:** M.JOYCE

**ITEM REF :** 307038

PAGE 2 OF 2

