

GOLD SEALANT

Page: 1

Compilation date: 12/06/2017

Revision No: 6

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: GOLD SEALANT Product code: 301813

Synonyms: UNIVERSAL GOLD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Sealant.

1.3. Details of the supplier of the safety data sheet

Company name: Cedesa Ltd

	Chater Lea Buildings
	Icknield Way
	Letchworth
	Hertfordshire
	SG6 1WT
	UK
Tel:	+44 (0) 1462 480764
Fax:	+44 (0) 1462 679324
Email:	mike.joyce@cedesa.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0) 1462 480764

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture		
Classification under CLP: Flam. Liq. 1: H224; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066		
Most important adverse effects:	Repeated exposure may cause skin dryness or cracking. Extremely flammable liquid	
	and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.	
2.2. Label elements		
Label elements:		
Hazard statements:	EUH066: Repeated exposure may cause skin dryness or cracking.	
	H224: Extremely flammable liquid and vapour.	
	H319: Causes serious eye irritation.	
	H336: May cause drowsiness or dizziness.	
Hazard pictograms:	GHS02: Flame	
	GHS07: Exclamation mark	

GOLD SEALANT



Signal words: Danger Precautionary statements: P280: Wear protective gloves/protective clothing/eye protection/face protection. P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312: Call a if you feel unwell. P370+378: In case of fire: Use suitable extinguishing media for the surrounding fire to extinguish. 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ACETONE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	30-50%

Section 4: First aid measures

4.1. Description of first aid measures

-	ualty from exposure ensuring one's own safety whilst doing so. Consult a
-	ualty from exposure ensuring one's own safety whilst doing so. Consult a
3	
Ingestion: Wash out m	outh with water. Consult a doctor.
Eye contact: Bathe the ey	e with running water for 15 minutes. Consult a doctor.
immediately	with plenty of soap and water.
Skin contact: Remove all	contaminated clothes and footwear immediately unless stuck to skin. Wash

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

GOLD SEALANT

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

on intersolial precaditoris, protective equipment and emergency procedures	6.1. Person	al precautions	, protective equipmen	t and emergency procedures
--	-------------	----------------	-----------------------	----------------------------

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

GOLD SEALANT

7.2. Conditions for safe storage, including any incompatibilities

 Storage conditions:
 Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

ACETONE

Workplace exposure limits:

State 8 hour TWA 15 min. STEL 8 hour TWA 15 min. STEL UK 1210 mg/m3 3620 mg/m3

Respirable dust

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area. Ensure lighting and electrical
	equipment are not a source of ignition.
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency.
Hand protection:	Protective gloves.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Liquid	
Colour:	Yellow	
Odour:	Characteristic odour	
Viscosity:	Viscous	
Flammability limits %: lower:	2.15 upper:	13
Flash point°C:	<21 Vapour pressure:	185 @ 20'C
Relative density:	1.12	
9.2. Other information		

Other information: No data available.

GOLD SEALANT

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

 Skin contact:
 There may be irritation and redness at the site of contact.

 Eye contact:
 There may be irritation and redness. The eyes may water profusely.

 Ingestion:
 There may be soreness and redness of the mouth and throat.

 Inhalation:
 There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

 ediate effects:
 Immediate effects can be expected after short term exposure.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

GOLD SEALANT

Page: 6

Section 12: Ecological information 12.1. Toxicity Hazardous ingredients: ACETONE BLUEGILL (Lepomis macrochirus) LC50 8300 mg/l 12.2. Persistence and degradability Persistence and degradability: Biodegradable. 12.3. Bioaccumulative potential Bioaccumulative potential: No bioaccumulation potential. 12.4. Mobility in soil Mobility: Readily absorbed into soil. 12.5. Results of PBT and vPvB assessment PBT identification: This product is not identified as a PBT/vPvB substance. 12.6. Other adverse effects Other adverse effects: Negligible ecotoxicity. Section 13: Disposal considerations 13.1. Waste treatment methods **Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company. Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes. NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal. Section 14: Transport information 14.1. UN number UN number: UN1133 14.2. UN proper shipping name Shipping name: ADHESIVES (ACETONE) 14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: ||

GOLD SEALANT

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information	
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	EUH066: Repeated exposure may cause skin dryness or cracking.
	H224: Extremely flammable liquid and vapour.
	H225: Highly flammable liquid and vapour.
	H319: Causes serious eye irritation.
	H336: May cause drowsiness or dizziness.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.