

**SAFETY DATA SHEET**  
RED SILICONE SEALANT (PRESSURE PACK)

**Page:** 1  
**Compilation date:** 25/04/2016  
**Revision No:** 2

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** RED SILICONE SEALANT (PRESSURE PACK)  
**Product code:** 307841

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** PC1: Adhesives, sealants.

**1.3. Details of the supplier of the safety data sheet**

**Company name:** Cedesca Ltd  
Chater Lea Buildings  
Icknield Way  
Letchworth  
Hertfordshire  
SG6 1WT  
UK  
**Tel:** +44 (0) 1462 480764  
**Fax:** +44 (0) 1462 679324  
**Email:** [mike.joyce@cedesa.co.uk](mailto:mike.joyce@cedesa.co.uk)

**1.4. Emergency telephone number**

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CLP:** Skin Irrit. 2: H315; Eye Irrit. 2: H319; -: H229

**Most important adverse effects:** Pressurised container: May burst if heated. Causes skin irritation. Causes serious eye irritation.

**2.2. Label elements**

**Label elements:**

**Hazard statements:** H229: Pressurised container: May burst if heated  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.

**Hazard pictograms:** GHS07: Exclamation mark



**Signal words:** Warning

**Precautionary statements:** P102: Keep out of reach of children.

# SAFETY DATA SHEET

## RED SILICONE SEALANT (PRESSURE PACK)

Page: 2

- P103: Read label before use.
- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P251: Do not pierce or burn, even after use.
- P264: Wash contaminated skin thoroughly after handling.
- P280: Wear protective gloves/protective clothing/eye protection/face protection.
- P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P332+313: If skin irritation occurs: Get medical advice/attention.
- P337+313: If eye irritation persists: Get medical advice/attention.
- P362: Take off contaminated clothing.
- P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### METHYLTRIACTOXYSILANE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	4253-34-3	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319; STOT SE 3: H335	1-10%

##### 1,1,1,2-TETRAFLUORETHAN

212-377-0	811-97-2	Substance with a Community workplace exposure limit.	-	1-10%
-----------	----------	--	---	-------

##### PROPYLTRIACTOXYSILAN

241-816-9	17865-07-5	-	Skin Corr. 1B: H314; -: EUH014	1-10%
-----------	------------	---	--------------------------------	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes.

**Ingestion:** Wash out mouth with water.

**Inhalation:** Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

[cont...]

**SAFETY DATA SHEET**  
RED SILICONE SEALANT (PRESSURE PACK)

Page: 3

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Immediate / special treatment:** Not applicable.

**Section 5: Fire-fighting measures**

**5.1. Extinguishing media**

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used.

**5.2. Special hazards arising from the substance or mixture**

**Exposure hazards:** In combustion emits toxic fumes.

**5.3. Advice for fire-fighters**

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**Section 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions:** Refer to section 8 of SDS for personal protection details.

**6.2. Environmental precautions**

**Environmental precautions:** Do not discharge into drains or rivers.

**6.3. Methods and material for containment and cleaning up**

**Clean-up procedures:** Wash the spillage site with large amounts of water.

**6.4. Reference to other sections**

**Reference to other sections:** Refer to section 8 of SDS.

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

**Handling requirements:** Avoid the formation or spread of dust in the air.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in a cool, well ventilated area.

**7.3. Specific end use(s)**

**Specific end use(s):** No data available.

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

[cont...]

**SAFETY DATA SHEET**  
RED SILICONE SEALANT (PRESSURE PACK)

Page: 4

**Hazardous ingredients:**

1,1,1,2-TETRAFLUORETHAN

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	4240 mg/m <sup>3</sup>	-	-	-

**DNEL/PNEC Values**

**DNEL / PNEC** No data available.

**8.2. Exposure controls**

**Respiratory protection:** Respiratory protective device with particle filter.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Section 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**State:** Liquid

**Colour:** Dark red

**Odour:** Characteristic odour

**Evaporation rate:** No data available.

**Oxidising:** No data available.

**Solubility in water:** Not miscible

**Viscosity:** No data available.

**Boiling point/range°C:** >35

**Melting point/range°C:** No data available.

**Flammability limits %: lower:** No data available.

**upper:** No data available.

**Flash point°C:** >93

**Part.coeff. n-octanol/water:** No data available.

**Autoflammability°C:** No data available.

**Vapour pressure:** No data available.

**Relative density:** 1.08

**pH:** No data available.

**VOC g/l:** No data available.

**9.2. Other information**

**Other information:** No data available.

**Section 10: Stability and reactivity**

**10.1. Reactivity**

**Reactivity:** Stable under recommended transport or storage conditions.

**10.2. Chemical stability**

**Chemical stability:** Stable under normal conditions.

[cont...]

**SAFETY DATA SHEET**  
RED SILICONE SEALANT (PRESSURE PACK)

Page: 5

**10.3. Possibility of hazardous reactions**

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

**10.4. Conditions to avoid**

**Conditions to avoid:** Heat.

**10.5. Incompatible materials**

**Materials to avoid:** Strong oxidising agents. Strong acids.

**10.6. Hazardous decomposition products**

**Haz. decomp. products:** In combustion emits toxic fumes.

**Section 11: Toxicological information**

**11.1. Information on toxicological effects**

**Relevant hazards for substance:**

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

**Symptoms / routes of exposure**

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Section 12: Ecological information**

**12.1. Toxicity**

**Ecotoxicity values:** No data available.

**12.2. Persistence and degradability**

**Persistence and degradability:** Biodegradable.

**12.3. Bioaccumulative potential**

**Bioaccumulative potential:** No bioaccumulation potential.

**12.4. Mobility in soil**

**12.5. Results of PBT and vPvB assessment**

**PBT identification:** This product is not identified as a PBT/vPvB substance.

**12.6. Other adverse effects**

**Other adverse effects:** Negligible ecotoxicity.

[cont...]

**SAFETY DATA SHEET**  
RED SILICONE SEALANT (PRESSURE PACK)

Page: 6

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

**14.1. UN number**

**UN number:** UN1950

**14.2. UN proper shipping name**

**Shipping name:** AEROSOLS (IATA ONLY), NON-FLAMMABLE

**14.3. Transport hazard class(es)**

**Transport class:** 2.2

**14.4. Packing group**

**14.5. Environmental hazards**

**Environmentally hazardous:** No

**Marine pollutant:** No

**14.6. Special precautions for user**

**Special precautions:** No special precautions.

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**15.2. Chemical Safety Assessment**

**Section 16: Other information**

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH014: Reacts violently with water.

H229: Pressurised container: May burst if heated

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.