

ALL PURPOSE ADHESIVE

Page: 1

Compilation date: 01/08/16

Revision No: 9

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: ALL PURPOSE ADHESIVE

Product code: 301160

Synonyms: 36-40003

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: Cedesa Ltd

	Chater Lea Buildings		
	Icknield Way		
	Letchworth		
	Hertfordshire		
	SG6 1WT		
	UK		
Tel:	+44 (0) 1462 480764		
Fax:	+44 (0) 1462 679324		
Email:	mike.joyce@cedesa.co.uk		

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066

Most important adverse effects: Repeated exposure may cause skin dryness or cracking. Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.

2.2. Label elements

Label elements:	
Hazard statements:	EUH066: Repeated exposure may cause skin dryness or cracking.
	H225: Highly flammable liquid and vapour.
	H319: Causes serious eye irritation.
	H336: May cause drowsiness or dizziness.
Hazard pictograms:	GHS02: Flame
	GHS07: Exclamation mark



ALL PURPOSE ADHESIVE

	Signal words:	Danger
	Precautionary statements:	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition
		sources. No smoking.
		P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.
		P271: Use only outdoors or in a well-ventilated area.
		P243: Take precautionary measures against static discharge.
		P280: Wear protective gloves/protective clothing/eye protection/face protection.
		P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.
		Rinse skin with water/shower.
		P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
		P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove
		contact lenses, if present and easy to do. Continue rinsing.
		P312: Call a POISON CENTER/doctor//if you feel unwell.
		P370+378: In case of fire: Use suitable extinguishing media for the surrounding fire to
		extinguish.
~		

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ACETONE

EINECS	CAS	PBT / WEL	CLP Classification	Percent	
200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	45.000%	

ETHYL METHYL KETONE

201-159-0	78-93-3	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	45.000%
			STOT SE 3: H336; -: EUH066	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash	
	immediately with plenty of soap and water.	
Eye contact:	Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist	
	examination.	
Ingestion:	Consult a doctor. If conscious, give half a litre of water to drink immediately. Do not	
	induce vomiting. Transfer to hospital as soon as possible.	
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a	
	doctor.	[c

ALL PURPOSE ADHESIVE

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be vomiting. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes. Vapour may travel considerable distance to source of

ignition and flash back. Highly flammable. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Refer to section 13 of SDS for suitable method of disposal.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

ALL PURPOSE ADHESIVE

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is forbidden.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Ensure lighting and electrical equipment are not a source of ignition.
 Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace	exposure	limits:
-----------	----------	---------

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	600mg/m3	900mg/m3	-	-

Respirable dust

Respirable dust

Hazardous ingredients:

ACETONE

Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1210 mg/m3	3620 mg/m3	-	-

ETHYL METHYL KETONE

UK	600 mg/m3	899 mg/m3	-	-
----	-----------	-----------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls			
Engineering measures:	Ensure there is sufficient ventilation of the area. The floor of the storage room must be		
	impermeable to prevent the escape of liquids.		
Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Gas/vapour			
	filter, type A: organic vapours (EN141). Compressed airline breathing apparatus		
	(EN139).		
Hand protection:	Protective gloves. Viton gloves.		
Eye protection:	Safety glasses. Ensure eye bath is to hand.		
Skin protection:	Protective clothing.		

ALL PURPOSE ADHESIVE

Page: 5

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties					
State:	Liquid				
Colour:	Colourless				
Odour:	Perceptible odour				
Evaporation rate:	Fast				
Solubility in water:	Insoluble				
Viscosity:	Non-viscous				
Boiling point/range°C:	56 Flammability limits %: lower:	0.6			
upper:	13 Flash point°C:	-19			
Autoflammability°C:	515Relative density:	0.86			

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
-------	---------	------	-------	-------

ALL PURPOSE ADHESIVE

Page: 6

ORL RAT	Г LD50	>5000	mg/kg
---------	--------	-------	-------

Hazardous ingredients:

ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

ETHYL METHYL KETONE

	IPR
--	-----

Relevant hazards for substance:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be vomiting. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

ACETONE

BLUEGILL (Lepomis macrochirus)	LC50	8300 mg/l	

12.2. Persistence and degradability

Persistence and degradability: Biodegradable in part only.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Volatile.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

ALL PURPOSE ADHESIVE

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

 Disposal operations:
 Transfer to a suitable container and arrange for collection by specialised disposal company.

 Disposal of packaging:
 Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1133

14.2. UN proper shipping name

Shipping name: ADHESIVES

(ACETONE; ETHYL METHYL KETONE)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

ALL PURPOSE ADHESIVE

Page: 8

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.