

## Fabric Glue – 301409 Technical Data Sheet

### Description:

Fabric Glue is especially suitable for use on porous materials such as fabrics, leather, cardboard and paper. It's high viscosity makes it clean to use, bonding time is short and the resultant bonds have reasonable heat and water resistance.

### Physical Characteristics:

|   |                        |
|---|------------------------|
| Appearance  | White liquid           |
| Base  | Natural rubber latex   |
| Viscosity   | 15,000 cPs (approx)    |
| Solid Content                                     | 60% (approx)           |
| Specific Gravity                                  | 0.94 (approx)          |
| Shelf Life (Under Recommended Storage Conditions) | 12 months              |
| Any other essential data                          | NOT FREEZE/THAW STABLE |

### Recommended Usage:

Apply Fabric Glue to one or both substrates depending on porosity.  
Bring surfaces together any time between applying adhesive and complete drying of the film.  
Press the two surfaces together with firm positive pressure.

### Important Note

Whilst all reasonable care is taken in compiling technical data on the company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company. It is the customer's responsibility to satisfy themselves self that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable and that in the light of continued research and development the information relating to each product has not been superseded.

### Precautions in Use:

**Important:** For full details please refer to the separate *Material Safety Data Sheet* for this Product  
Fabric Glue is not classified as dangerous according to EU Directive 1999/45/EC and does not require any special labelling.

### Environmental and Waste Issues:

Residues should be disposed of in accordance with local authority guidelines.

### Storage:

To ensure safe storage of Fabric Glue containers should be well sealed to prevent evaporation of water and the formation of skin on the surface. The adhesive must be stored at a temperature above freezing. A temperature of 10 – 25°C for not more than 12 months is recommended. Higher temperatures will affect quality and cause the formation of crusts and skins, especially if the containers are not tightly closed or subjected to direct sunlight for long periods.

|         |       |          |          |           |
|---------|-------|----------|----------|-----------|
| TDS NO. | ISSUE | DATE:    | PAGE NO. | ISSUED BY |
| 301409  | 3     | 13/05/12 | 1 OF 1   | M.Joyce   |